



ProMAG®

Magnetic Sheeting

Our ProMAG® Magnetic Sheet is ready for you! Purchase stock rolls in a variety of thicknesses.



MAGNETIC STRENGTHS: All ProMAG® Magnetic Sheet is available in standard magnetic strength. Our magnetic sheeting can be magnetized single sided or double sided for thickness above .030". Non-magnetized sheeting is also an option.

PRODUCT FLEXIBILITY: At 68° F (20° C), our high-quality magnetic material can be coiled to a 1/2" (12.7 mm) radius without cracking.

TEMPERATURE: ProMAG® magnet is designed to perform in temperatures ranging from -15°F to 160°F (-26° C to 71° C).

PRODUCT THICKNESS: The wide range of thicknesses available in ProMAG® Magnetic Sheet can be your competitive edge. ProMAG® Magnetic Sheet is available in thicknesses of .015" to .060".

LAMINATES: ProMAG® magnetic sheet is available with the following colored vinyls:

- matte white
- black
- blue
- yellow
- gloss white
- red
- green

TECHNICAL DATA:

- Available in both rolls and sheets. Standard roll width is 24 3/8".
- ProMAG® Magnetic Sheet products are magnetized with equally spaced magnetic poles running parallel to the length of the rolls.

TECHNICAL SUPPORT: More than 35 years of combined experience, innovation and research allow Magnum to offer the finest technical support and service in the magnet industry.



Magnum Magnetics®

The Force in Flexible Magnetics.

801 Masonic Park Road • Marietta, OH 45750
Phone: 740.373.7770 • Fax: 740.373.2880



Quality Made
in the USA

STANDARD PRODUCTS

PRODUCT CODE	DESCRIPTION	LAMINATE
Cut Blanks		
A030VMWE24.37P18.00000SH1	.030" x 24 3/8" x 18"	Matte White Vinyl
A030VMWE24.37P12.00000SH1	.030" x 24 3/8" x 12"	Matte White Vinyl
A030VMWE12.00P18.00000SH1	.030" x 12" x 18"	Matte White Vinyl
Rolls		
A030NONE24.37N00000050SHP	.030" x 24 3/8" x 50'	Plain (uncoated)
A015VMWE24.37N00000050SJP	.015" x 24 3/8" x 50'	Matte White Vinyl
A020VMWE24.37N00000050SJP	.020" x 24 3/8" x 50'	Matte White Vinyl
A020VMWE24.37N00000050SJ1	.020" x 24 3/8" x 50'	Matte White Vinyl (plain box-no identification)
A030VMWE24.37N00000010SHP	.030" x 24 3/8" x 10'	Matte White Vinyl
A030VMWE24.37N00000025SHP	.030" x 24 3/8" x 25'	Matte White Vinyl
A030VMWE24.37N00000050SHP	.030" x 24 3/8" x 50'	Matte White Vinyl
A030VMWE24.37N00000050SH1	.030" x 24 3/8" x 50'	Matte White Vinyl (plain box-no identification)
A030VBLK24.37N00000010SHP	.030" x 24 3/8" x 10'	Black Vinyl
A030VBLK24.37N00000050SHP	.030" x 24 3/8" x 50'	Black Vinyl
A030VAYG24.37N00000010SHP	.030" x 24 3/8" x 10'	Yellow Vinyl
A030VAYG24.37N00000050SHP	.030" x 24 3/8" x 50'	Yellow Vinyl
A030VWHG24.37N00000025SHP	.030" x 24 3/8" x 25'	Gloss White-Top coated
A030VWHG24.37N00000050SHP	.030" x 24 3/8" x 50'	Gloss White-Top coated
A015ASIA24.37N00000050SJP	.015" x 24 3/8" x 50'	Standard Adhesive
A020ASIA24.37N00000050SJP	.020" x 24 3/8" x 50'	Standard Adhesive
A025ASIA24.37N00000050SHP	.025" x 24 3/8" x 50'	Standard Adhesive
A030ASIA24.37N00000050SHP	.030" x 24 3/8" x 50'	Standard Adhesive

SHEET MAGNETIZATION INFORMATION

THICKNESS	POLE SPACING	AVERAGE MAGNETIC PULL*
.015"	16 ppi	50 lbs.
.020"	16 ppi	75 lbs.
.025"	12 ppi	85 lbs.
.030"	12 ppi	100 lbs.
.045"	10 ppi	110 lbs.
.060"	10 ppi	145 lbs.

*Per square foot standard energy with zero air gap.
Average Magnetic Pull figures are based upon internal test data.

Visit www.magnummagnetics.com for complete care and cleaning instructions.



The Force in Flexible Magnetics

800.258.0991
sales@magnummagnetics.com
magnummagnetics.com

"The Force in Flexible Magnetics", "Magnum", "Magnum Magnetics" and the "M" and arrow symbol, individually and in combination, as well as DigiMag, are U.S. registered trademarks of Magnum Magnetics Corporation.